

Beacon LED Tower

The Lind Equipment **Award Winning** Beacon LED Tower brings you all the light you've come to expect from traditional 4x1000W metal halide light towers, but in a completely unexpected package. **Compact, lightweight, and truly man-portable**, the Beacon LED Tower can be transported with ease without any compromise in durability and stability.

The Beacon LED Tower uses **direct drive high-efficiency LED lights** and runs whisper-quiet on any power source you choose: external, a user supplied generator or a fuel tank. **Operating costs of as little as \$0.10 / hour** and with state-of-the-art robust LED lighting - the tower is virtually maintenance free.

A Beacon LED Tower can be lifted into the back of a pick-up truck, and two towers can fit in the truck bed for easy transportation. The steel frame chassis and mast are robust enough to withstand any job site condition. The Beacon LED Tower can be purchased in lay-flat models or in vertical mast models to fit any application.

AWARDS



KEY BENEFITS

- Whisper-quiet operation
- Incredibly easy deployment
- Very low maintenance required
- Ability to daisy-chain multiple towers and tools
- 2 Towers can run on a 15A circuit
- Use with 'suitcase' type generators, or run off external power
- Direct Drive high-efficiency LED lighting


HALF the cost of light
traditional towers

* Made in Canada & the U.S.A.



LE980LEDV-T4

Four Ultra Efficient LED Lights
Two light head option available!



Available in Yellow or Black

Beacon LED Tower

SPECIFICATIONS		LE980LEDV-T2	LE980LEDV-T4
Description of the Tower		Two-light Vertical Mast	Four-light Vertical Mast
Colour Choice		Add '-B' for the black colour model, add nothing for yellow	
Lights	Power	400W	800W
	Amperage	3.3 Amps @120V	6.7 Amps @120V
	Lumens	60,000	120,000
	Voltage	90V-277V	
	Ingress protection	IP65 Weatherproof	
	Construction	Aluminum housing, polycarbonate lenses	
	Rated hours	Over 50,000	
	Approvals	cETLus/IP65	
Mast	Max height	16' (from the ground)	
	Construction	Steel	
	Wind resistance	45 mph	
Chassis	Construction	Steel frame	
	Outriggers	Outriggers extend to 2' beyond frame	
	Tires	Foam-filled rubber tires	
	Features	Caster wheels • Side access forklift guides	
	Dimensions (stowed)	L: 52" • W: 39"(32" fully in) • H: 82"	
	Weight	350 lbs	380 lbs
Cabinet	Construction	Steel	
	Internal dimensions	L: 27" • W: 21" • H: 19.5"	
	Features	Lockable • Ventilated • On/off switch • Daisy-chain outlet	
Fuel Tank	Dimensions	L: 19.3" • W: 12.2" • H: 10.2"	
	Capacity	6 Gallons • 23 Litres	
	Features	• Comes complete with hose and fuel cap that will fit most popular suitcase generator models. Alternative cap sizes available - call Lind • Removable auxiliary tank	
	Run time	Approx 45 hours on standard 2000W suitcase generator with auxiliary fuel tank	
Generator	Units do not come standard with a suitcase generator. Lind can also supply for additional cost.		